

DALI MASTER CONTROLLER

DALI 64 Channels module

Data Sheet Rev 3.2

Model: TIS-DALI-64







OVERVIEW

DALI 64 module monitors and controls all lights (including florescent, LED, and more), ballasts, and drivers that are connected to DALI network. This interface supports 64 channels, and if looped together using the TIS BUS system can control more channels in the same network.


KEY BENEFITS

- 64 channels controller
- Channel, scene, groups, and parameters setting
- Configurable with external DALI power supply (optional)

KEY FEATURES

- Standard 35 mm din rail
- Built-in DALI power supply
- ★ Works with TIS-BUS protocol







DALI MASTER CONTROLLER


TIS – DALI 64 CHANNELS MODULE


Model: TIS-DALI-64





PRODUCT SPECIFICATIONS			
ф	Ports	DALI	Standard DALI connection Numbers of units max 64 units
(TISBUS)	TIS Bus	Number of devices on 1 line Bus voltage Current consumption Protection	Max. 64 12-32 V DC <300 mA / 24 V DC Reverse polarity protection
(Reaction time		approx. 20ms
o,	Function programmable options	DALI	Numbers of addresses 64 16 Groups 16 Scenes
Îo	Mounting	Din Rail Wall mount	Standard 35 mm Din rail screw holder on the back of the module
	Connection terminal	Load and Power Data / bus	Screw terminal 0,254mm2 Male female connectors Link + screw Terminal
Řej	Weight	Without packaging	0.21 KG
+	Dimensions	Width \times length \times height	90mm × 73mm × 76mm
	Housing	Materials Casing color IP rating	Fire-proof ABS Black Gray IP 20
	Temperature range	Operation Storage Transport	-3060°C -2060°C -3075°C
8	Air humidity		<85% non-condensing







TIS Logo is a Registered Trademark of Texas Intelligent System LLC in the United States of America. This company takes TIS Control Ltd. in other countries. All of the Specifications are subject to change without notice.