

TIS IO OUTDOOR BELL PANEL

Data Sheet Rev 3.2

Model: IO-OUT-HOTEL





OVERVIEW

Our IO Outdoor Bell unit features access control, a push bell button, and DND, room number & service indicators. This wall-mount panel is perfect for hotels.

KEY BENEFITS

- Room number display
- Hotel service indicator
- Programmable RGB backlite
- Push bell button with built-in relay switch

KEY FEATURES

- Wall-mount panel
- Works with TIS-BUS protocol
- 4 Digital inputs for service button connection
- Fits in all standard back boxes (US, UK, EU)











TIS IO OUTDOOR BELL PANEL



Model: IO-OUT-HOTEL



PRODUCT SPECIFICATIONS			
<u>+</u>	Input	Dry Inputs	4 Digital Inputs
<u> </u>	Output	Low current relay	1 Relay Output 2A/12V
(TISBUS)	TIS Bus	Number of devices on 1 line Bus voltage Current consumption	Max. 64 12-32 V DC <25 mA / 24 V DC
3	Protection		Reverse Polarity Protection ESD Protection
(Reaction time		approx. 20ms
To	Mounting	Wall mount	by 2 screws on the back box (UK, Europe, US)
===	Connection terminal	Data	2 mail pins connectors to fit in panel addition
† !†	Operating and display elements	Push buttons Backlight TIS bus Upgrading	push button with Red / White Indicator RGB indicators + Room number white LEDs TIS Protocol messages and commands By Rs485 upgrading kit.
\$ 0	Functions	Bell Press	Push Button
å	Weight	Without packaging	120 g
<u></u>	Dimensions	Width \times Length \times Height	90mm(94mm peak) × 13mm × 129mm
	Housing	Materials Casing color Internal Parts color IP rating	PC fire proof / acrylic in front Silver plating frame. Glass black Black & White IP 50
	Temperature range	Operation Storage Transport	-1060°C -2050°C -2575°C
A			





<80% non-condensing



a

Air humidity