

TIS IO CARD SWITCH

Data Sheet Rev 3.2

Model: IO-CARD-3SRV







OVERVIEW

IO card switch acts as an RF card reader with logic to offer the best energy savings for hospitality systems. Additionally, it has 3 touch buttons for Do not disturb (DND), Make up room (MUR), and Laundry.

KEY BENEFITS

- RF card reader and access control
- Built-in advanced logic
- v3 push buttons for hotel services

KEY FEATURES

- Wall mount panel
- Works with TIS-BUS Protocol
- Fits all standard backbox sizes (US, UK, EU)












TIS IO CARD SWITCH



Model: IO-CARD-3SRV



PRODUCT SPECIFICATIONS			
<u>+</u>	Input	RF card reader	Temic RF Type
<u> </u>	Output	Relay	1x relay 1A/220V
(TISBUS)	TIS Bus	Number of devices on 1 line Bus voltage Current consumption	Max. 64 12-32 V DC <25 mA / 24 V DC
3	Protection		Reverse Polarity Protection ESD Protection
(Reaction time		approx. 20ms
To	Mounting	Wall mount	by 2 screws on the back box (UK, Europe, US)
	Connection terminal	Data	2 mail pins connectors to fit in panel addition
†‡†	Operating and display elements	Push Buttons Card switch TIS bus Upgrading	3× push button with Orange / White LEDs Card RF reader TIS Protocol messages and commands By Rs485 upgrading kit.
Q o	Functions	CARD Switch 3 Push Buttons	To turn off lights if no occupancy or if card removed. For DND, MUR ad Laundry request
Å	Weight	Without packaging	120 g
1	Dimensions	Width × Length × Height	129mm × 20mm(including card holder) × 94mm
	Housing	Materials Casing color Internal Parts color IP rating	PC fire proof / acrylic in front Silver plating frame. Glass black or white Black & White IP 50
	Temperature range	Operation Storage Transport	-1060°C -2050°C -2575°C
8	Air humidity		<80% non-condensing





TIS Logo is a Registered Trademark of Texas Intelligent System LLC in the United States of America. This company takes TIS Control Ltd. in other countries. All of the Specifications are subject to change without notice.