

### **LUNA OUTDOOR BELL PANEL**

Outdoor bell panel

Model: LUNA-3S-Bell

Data Sheet Rev 3.1







## **OVERVIEW**

TIS Luna Outdoor Bell Panel features a touch bell button and 3 indicators for hotel services; Do not disturb (DND), Make up room (MUR) and Laundry. Its design also allows hotel room number display at day and night.

#### **KEY BENEFITS**

- Hotel room and services indicator.
- RGB programmable backlit for the DND, MUR and Laundry
- Touch bell button with built-in relay switch

#### **KEY FEATURES**

- ★ Wall mount, Panel
- Works with TIS-BUS Protocol
- ★ 4 digital inputs for service button connection.
- ★ Fits into all back box standard sizes (US, UK, EU)







# LUNA BEDSIDE PANEL Bedside Touch Panel

Model: LUNA-BEDSIDE



PRODUCT SPECIFICATIONS			
•	Touch	Active area Touch Type	1 button for bell Capacitive
<u>+</u>	Input	Using Panel Addition	4 Digital Inputs
<u>.</u>	Output	Low current relay	1 Relay Output 2A/12V
TISBUS	TIS Bus	Number of devices on 1 line Bus voltage Current consumption	Max. 64 12-32 V DC <25 mA / 24 V DC
<b>©</b>	Protection		Reverse Polarity Protection ESD Protection
( <del>)</del>	Reaction time		approx. 20ms
ĵo	Mounting	Wall mount	2 screws on the back box (UK, Europe, US)
200	Connection terminal	Data	2 mail pins connectors to fit in panel addition
†‡†	Operating and display elements	touch buttons Backlight TIS bus Upgrading	1 touch button 3 RGB indicators + Room number white LEDs TIS Protocol messages and commands By Rs485 upgrading kit.
<b>⇔</b> °	Functions	Bell Press	Touch Button
å	Weight	Without packaging	120 g
1	Dimensions	Width $\times$ length $\times$ height	90mm (94mm peak) × 129mm × 13mm
	Housing	Materials Casing color Internal Parts color IP rating	PC fire proof / Glass in front Silver plating frame. Glass black Black & White IP 50
	Temperature range	Operation Storage Transport	-1060°C -2050°C -2575°C
	Air humidity		<80% non-condensing



