

LUNA OUTDOOR BELL PANEL

Outdoor bell panel with RFID

Data Sheet Rev 3.1

Model: LUNA-3S-Bell-RF



OVERVIEW

With our Luna Outdoor bell Panel, it act as RF Card reader and access control, Also it has touch bell button and 3 indicators for hotel Do not disturb (DND), Make up room (MUR) and Laundry.

((I cano te

KEY BENEFITS

- RF card Reader and Access Control
- Hotel Service indicators
- RGB programable backlite for the DND, MUR and Laundry
- Touch bell press with built in relay switch

KEY FEATURES

- 🛠 Wall mount, Panel
- ✤ Works with TIS-BUS Protocol
- ★ 4 digital inputs for service button connection.
- Fit in all backbox standard sizes (US, UK, EU)






LUNA BEDSIDE PANEL Outdoor bell panel with RFID

Model: LUNA-3S-Bell-RF

TFIS

| PRODUCT SPECIFICATIONS | | | |
|------------------------|--------------------------------|---|--|
| £ | Touch | Active area Touch Type | 1 button for bell Capacitive |
| Ļ | Input | RF card reader Using Panel Addition | Temic RF Type 4 Digital Inputs |
| Ţ. | Output | Low Current Relay | 1 Relay Output 2A/12V |
| (TI SBUS) | TIS Bus | Number of devices on 1 line Bus voltage Current consumption | Max. 64 12-32 V DC <25 mA / 24 V DC |
| ۲ | Protection | | Reverse Polarity Protection ESD Protection |
| () | Reaction time | | approx. 20ms |
| ĵo | Mounting | Wall mount | by 2 screws on the back box (UK, Europe, US) |
| | Connection terminal | Data | 2 mail pins connectors to fit in panel addition |
| †∔† | Operating and display elements | touch buttons Backlight TIS bus Upgrading | 1 touch button 3 RGB indicators + RFID icon white LEDs TIS Protocol messages and commands By Rs485 upgrading kit. |
| ¢ ° | Functions | Bell Press RFID | Touch Button Access Control |
| Ô | Weight | Without packaging | 120 g |
| Ŧ | Dimensions | Length \times Width \times Height | 129mm × 13mm × 90mm (94mm peak) |
| | Housing | Materials Casing color Internal Parts color IP rating | PC fire proof / Glass in front Silver plating frame. Glass black Black & White IP 50 |
| l | Temperature range | Operation Storage Transport | -1060°C -2050°C -2575°C |
| 8 | Air humidity | | <80% non-condensing |

((Come to



TEI

United States of America. This company takes Intelligent System LLC in the United States of America. This company takes TIS Control Ltd. in other countries. All of the Specifications are subject to change without notice.

SUITE# 610. 860 NORTH DOROTHY DR RICHARDSON TX 75081.USA

RM 1502-p9 Easey CommBldg 253-261 Hennessy Rd Wanchai Hong Kong

www.tiscontrol.com