TIIS Smart Home

	TIS M3 Curtain motor	Aluminum ally case Size 45*70*305mm	For TIS M3 Curtain use only
	Wheel box	Anti-aging POM material, maximum endure 1052 driver	For TIS M3 use; 2pcs for each one rail
	Rail	Low resistance low noise Each rail 2 meters	Suitable for M3、M7、 TIS Motors. standard length-140mm
0000	Pulley	To drag the hangings	Suitable for M3、M7、 TIS Motors,1pc for single track, 2pcs for double track
9.0	Curve pulley	To drag the hangings	Suitable for M3、M7、 TIS Motors , 1pc for single track, 2pcs for double track

TIIS Smart Home

12mm tooth belt	Using effect will be better after oil immersion	Belt length= rail net length*2+ 48 belt teeth grid.
Ceiling Mounting kits	Stainless steel material For ceiling rail installation	2∼3 pcs for each meter of rail
T shape Wall mounting kits	For Wall mounting	Wall installation, need to be used along with the ceiling mounting kits
Wheels	Smooth, silent	$6\sim$ 8 pcs for each meter of rail
Rail connector	For connecting rails if your curtain more than 2 meters	1pc for 1 connecting port

TIIS Smart Home

Wheel box hook	Install into different positions of wheel box to hang the curtains.	1∼3 pcs for the motor wheel box, but not for another side which with no motor
Clamping lug	To fix the rail and wheel box, can hang the cloth.	1pc for single track rail; 2pcs for double track rail
Clamp	To fix the rail and wheel box, Use for keeping off the pulley of single track rail only. Can not hang the cloth.	1pc for single track rail; Not for double track rail
Round ceiling kits	For ceiling mounting of the rail. Normally install the round ceiling kits to the ceiling first.	2∼3pcs per meter of rail.
Belt Jointers	Use to joint the 2 ends of the belt inside the rail	2 sets per belt.