

### TIS SECURITY MODULE

Data Sheet Rev 3.2

Model: TIS-SEC-SM







## **OVERVIEW**

This module is capable of covering more than 3000 BUS inputs divided into 8 areas to enhance security of house in many aspects. TIS Security Module allows automatic arm/disarm in different modes, including vacation, away, day, or night as it is equipped with a built-in clock.

#### **KEY BENEFITS**

- Arm/Disarm security system in 5 modes (vacation, away, night, day, OFF)
- Auto arming/disarming in different modes
- Configurable with all sensors in TIS bus network.
- Arming and alarm log recording.
- Protection program available in vacation mode
- Advanced Commands for Arming/Alarm situation

#### **KEY FEATURES**

- Built-in timer with lasting battery.
- ★ Zone bypass function
- Standard 35 mm din rail
- Reverse Polarity Protection
- ★ Works with TIS-BUS protocol









# TIS SECURITY MODULE

Model: TIS-SEC-SM





PRODUCT SPECIFICATIONS			
6	Security	Levels Arming commands Alarm Commands Extra Alarms Sirens and buzzer	Vacation, Away, Night, Day, Disarm 20 for each level 20 for each alarm type Panic, blackout, freezing temperature, 3 channels addressable. (Burglary, Fire, Buzzer)
(TISBUS <sub>)</sub>	TIS Bus	Number of devices on 1 line Bus voltage Current consumption Protection	Max. 64 12-32 V DC <25 mA / 24 V DC Reverse polarity protection
<b>(</b>	Reaction time		approx. 30ms
o o	Function programmable options	Other Functions	Auto arm/disarm, entry /exit delay, dial out time, zone auto bypass, duress alarm
To	Mounting	Din Rail Wall mount	Standard 35 mm Din rail screw holder on the back of the module
	Connection terminal	Load and Power Data / bus	Screw terminal 0,254mm2  Male female connectors Link + screw Terminal
kg	Weight	Without packaging	0.22 KG
1	Dimensions	Width $\times$ length $\times$ height	90mm × 73mm × 76mm
	Housing	Materials Casing color IP rating	Fire-proof ABS Black Gray IP 20
ı	Temperature range	Operation Storage Transport	-3060°C -2060°C -3075°C
	Air humidity		<85% non-condensing





