

TIS 4 DIGITAL INPUT MODULE

4 Zones Dry Inputs

Data Sheet Rev 3.1

Model: TIS-4DL-IN







OVERVIEW

This small module is used to connect different types of digital sensors that usually work in a NO/NC (Normally Open/Normally Close) structure in a home's smart network.

Also you can upgrade old wall switches/dimmers without extra cabling. There is no need to replace old switches with new ones. Just install our 4DI module and enjoy controlling your home with utmost convenience.

TIS_{Smal}

Tis

KEY BENEFITS

- Capability to connect any 3rd party NC/ NO sensors to TIS Network
- Monitor Home Security Zones
- Security and Safety upgrade and energy saving logic
- Convert normal light switches to smart ones

KEY FEATURES

- ★ Free locate, small size module
- Works with TIS-BUS Protocol
- ★ 4 digital inputs for automation and security use
- ★ Used for light ON/OFF/dimming









TIS 4 DIGITAL INPUT MODULE



4 Zones Dry Inputs Model: TIS-4DL-IN



| | | | S the change |
|----------------|--------------------------------|-------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| | PRODUCT SPECIFICATIONS | | |
| <u>+</u> | Input | Number of channels Input Type Length of connected wire | 4 Digital input. Open / Close < 350 meter |
| (TI SBUS) | TIS Bus | Number of devices on 1 line Bus voltage Current consumption | Max. 64 12-32 V DC <12 mA / 24 V DC |
| © | Protection | Bus connection Digital input | Reverse Polarity Protection Low voltage <24V Protection |
| () | Reaction time | | approx. 20ms |
| ĵo | Mounting | Can be installed anywhere | 2 screws required |
| | Connection terminal | Data / bus | Screw terminal 0.252.5mm2 |
| †‡† | Operating and display elements | Programming button/LED By TIS bus Upgrading | For assignment of the physical address TIS Protocol messages and commands 1 X mini USB for latest upgrade. |
| o°. | Functions for each zone | Digital input Open Digital input close Revers control | 20 commands 20 commands 1 command |
| å | Weight | Without Packaging | 0.1 KG |
| 1 | Dimensions | Width \times Length \times Height | 46mm × 46mm × 16mm |
| | Housing | Materials Casing color IP rating | ABS Fireproof Dark Gray IP 20 |
| | Temperature range | Operation Storage Transport | -1050°C -2050°C -2575°C |
| | Air humidity | | <85% non-condensing |



