

WIRELESS ADS DIMMER

Wi-Fi Single Input Controller

Models: ACM-1D-2Z

Data Sheet Rev 3.2







OVERVIEW

The ADS Dimmer is a Wi-Fi enabled universal dimmer module with remote control capability over the internet via the TIS app.

This solution features a dry input particularly designed to be coupled with any push-button wall switch for limitless light control.

KEY BENEFITS

- Built-in Wi-Fi; links directly to the Internet
- Universal dimmer can dim most types of lights
- Control by TIS app, locally or remotely

KEY FEATURES

- 2 digital inputs (dry input)
- Works with TIS-BUS Protocol
- Small size; can be located anywhere









WIRELESS ADS DIMMER


Wi-Fi Single Input Controller


Models: ACM-1D-2Z





		PRODUCT SPECIFICA	TIONS	
4	Power supply	Input Voltage Output Power Protection Current consumption	110-230 VAC 50/60 Hz 3W / 12V Built in Protection fuse 10-20 mA / 12 V DC	
Ţ	Output	Number of channels Nominal voltage Nominal current per channel Lighting Incandescent Lamp LED (dimmable) CFL (dimmable)	1 110 / 230 V AC 50/60 Hz 500 Watts 300 Watts 300 Watts	
TISÂÎR	TIS AIR	WIFI Signal Protocol Standard	2.4 GHz 802.11 b/g/n	
()	Reaction time		approx. 30ms	
ĵo	Mounting	Free locate	Can be installed anywhere	
†‡†	Operating and display elements	Digital Inputs TIS AIR PRG Button with LED Upgrading	2 dry inputs for control TIS Protocol messages and commands Programming button and status LED. By WIFI Connection	
å	Weight	Without packaging	10 g	
1	Dimensions	(Width \times Length \times Height)	49mm × 20mm × 49mm	
	Housing	Materials Internal Parts color IP rating	PC fire proof White IP 50	
	Temperature range	Operation Storage Transport	-1060°C -2050°C -2575°C	
8	Air humidity		<80% non-condensing	







TIS Logo is a Registered Trademark of Texas Intelligent System LLC in the United States of America. This company takes TIS Control Ltd. in other countries. All of the Specifications are subject to change without notice.