

## TIS WI-FI INFRARED EMITTER

IR Emitter with Temperature Sensor

Model: AIR-1IRE-T

### Data Sheet Rev 3.2







## **OVERVIEW**

This wireless product has an infrared emitter port and a temperature sensor. This means that you can control any infrared device easily and remotely, and if you want to manage your home's AC, the temperature sensor is there to assist you, making sure that no energy is wasted and the room temperature is always suitable for you. This controller is also compatible with any universal brand such as Samsung, Sony, LG, etc.

#### **KEY BENEFITS**

- Controls Split AC via TIS App
- Controls Media appliances such as TV, DVD, and TV Box
- ◆ Monitors Room Temperature
- Sends Alerts in Case Temperature Goes So High or Low

#### **KEY FEATURES**

- Free locate, Small size Module
- Built-in Wi-Fi
- Features a database with more than 1000 IR Codes
- Capability to learn up to 200 more IR codes via the TIS IR Learner








# TIS WI-FI INFRARED EMITTER

IR Emitter with Temperature Sensor Model: AIR-1IRE-T





	PRODUCT SPECIFICATIONS		
*	Power Supply	Input Voltage Output Power Protection Current consumption	80-240 VAC 50/60 Hz 3W / 12V Built in Protection fuse 10-30 mA / 12 V DC
1	Output	IR Emitter Peak wave length Radiated emission power (Φe) Length of connected wire	940 nm 2,4 mW < 5 meters
τιςλΐr	TIS AIR	Wi-Fi Signal Protocol Standard	2.4 GHz 802.11 b/g/n
<b>②</b>	Protection	IR Emitter	Reverse Polarity Protection
( <del>)</del>	Reaction time		approx. 30ms
<b>F</b> o	Mounting	Din-Rail	Standard 35 mm Din rail
===	Connection terminal	Power Infrared	Screw terminal 0,252mm2 Female 4 pins connector
†‡†	Operating and display elements	Programming button Indicator LED Upgrading	For connecting to Wi-Fi router Blue and Red LED By Wi-Fi
<b>\$</b> 0	Functions	IR Codes	Can save up to 250 Codes
۵	Weight	Without packaging	100 gr
<b></b>	Dimensions	(Width $\times$ Length $\times$ Height)	50mm × 32mm × 54mm
	Housing	Materials Internal Parts color IP rating	PC fire proof White IP 20
	Temperature range	Operation Storage Transport	-1050°C -2050°C -2575°C
8	Air humidity		<85% non-condensing









TIS Logo is a Registered Trademark of Texas Intelligent System LLC in the United States of America. This company takes TIS Control Ltd. in other countries. All of the Specifications are subject to change without notice.

SUITE# 610. 860 NORTH DOROTHY DR RICHARDSON TX 75081.USA

RM 1502-p9 Easey CommBldg 253-261 Hennessy Rd Wanchai Hong Kong