

TIS WI-FI PLUG Portable Power Outlet Model: AIR-SOCKET-S

Data Sheet Rev 3.1

OVERVIEW

Equipped with an internal WI-FI, this solution is designed to be automatically connected to the Internet. TIS wireless socket enables you to control lights and any other electrical appliances that are connected to it.





TIS WI-FI PLUG

Portable Power Outlet

Model: AIR-SOCKET-S



ket to any ic heater ance and nywhere.	0	T18 •	0	22100

	PRODUCT SPECIFICATIONS						
4	Power supply	Input Voltage Output Power Protection Current consumption	110-230 VAC 50/60 Hz 3W / 12V Built-in protection fuse 20 mA / 12 V DC				
Ţ	Output	Number of channels Nominal voltage Nominal current per channel	1 110 – 230 V AC 50/60 Hz 10 A / 230 VAC				
Ţ	Output switching current	Max switching current Max Continues current Max. switching Voltage	16A/230 VAC Resistive 8A/230 VAC Florescent 10A/230 VAC 440VAC / 125VDC				
Ţ	Output service life	Mechanical Endurance	> 10,000,000 OPS				
Ţ	Output switching times	Operating time Releasing time Max. operating frequency	15 mS (at nomi. Volt) 8 mS (at nomi. Volt) 20 cycle/min				
тısÂîr	TIS AIR	WIFI Signal Protocol Standard	2.4 GHz 802.11 b/g/n				
¢	Reaction time		approx. 30ms				
·	Socket Type	Optional	Europe, UK, US or Universal type				
2000	Connection terminal	Data	Direct TIS bus connection				
ţ†	Operating and display elements	touch buttons Backlight TIS AIR Upgrading	1 Control Button LED Backlight Indicators TIS Protocol Messages & Commands By WIFI Connection				
Ô	Weight	Without packaging	20 g				
Ŧ	Dimensions	Length \times Width \times Height	62mm × 68mm × 102mm				



Copyright © 2020 TIS, All Rights Reserved TIS Logo is a Registered Trademark of Texas Intelligent System LLC in the United States of America. This company takes TIS Control Ltd. in other countries. All of the Specifications are subject to change without notice.

TEXAS INTELLIGENT SYSTEM LLC SUITE# 610. 860 NORTH DOROTHY DR RICHARDSON TX 75081.USA TIS CONTROL LIMITED RM 1502-p9 Easey CommBldg 253-261 Hennessy Rd Wanchai Hong Kong

TIS WI-FI PLUG Portable Power Outlet

Model: AIR-SOCKET-S





TIS

PRODUCT SPECIFICATIONS

	Housing	Materials Internal Parts color IP rating	PC fire-proof White IP 50
ß	Temperature range	Operation Storage Transport	-1060°C -2050°C -2575°C

٨ Air humidity <80% non-condensing





Copyright © 2020 TIS, All Hights Heserved TIS Logo is a Registered Trademark of Texas Intelligent System LLC in the United States of America. This company takes TIS Control Ltd. in other countries. All of the Specifications are subject to change without notice.

TEXAS INTELLIGENT SYSTEM LL SUITE# 610. 860 NORTH DOROTHY DR RICHARDSON TX 75081.USA

TIS CONTROL LIMITED RM 1502-p9 Easey CommBldg 253-261 Hennessy Rd Wanchai Hong Kong

www.tiscontrol.com