



TIS VIDEO DOOR PHONE

RF-enabled Intercom with Flush Buttons

Data Sheet Rev 3.1

Model: TIS-AP-CDM-18



OVERVIEW

The newly designed TIS-AP-CDM-18 is an IP video intercom equipped with a SIP system and an RF card reader and offers premium audio and video quality and real-time entrance monitoring. This door phone with a trendy waterproof aluminum panel and a numeric keypad can be flush mounted in any geographical location. Enhanced security and ease of mind are what this gadget allows for through high entrance monitoring. No matter where you are, this door phone makes it simple to see who is at the door.

KEY BENEFITS

- + Fast response time to visitors.
- + Increases building safety.
- + Two-way audio communication over the IP network.
- + Enables remote control.
- + Eliminates the need for the physical presence of the user.
- + Available for cold spots with an anti-cold version.

KEY FEATURES

- ★ Numeric keypad with extra buttons.
- ★ High-quality microphone, speaker, camera, etc.
- ★ 3rd-Party-Video components compatibility.
- ★ Flush-mounted.
- ★ RF card reader & Infrared sensor.



TIS VIDEO DOOR PHONE












RF-enabled Intercom with Flush Buttons



Model: TIS-AP-CDM-18



PRODUCT SPECIFICATIONS

	Input	Interface	Numeric keypad with extra buttons, 2M pixels camera
		Narrowband & Broadband audio codecs DC	G.711a, G.711μ, G.729 & G.722 12 V DC (without PoE)
	Output	Relays	3
		Power out	12V/400mA
	Network	Protocols support	IPv4, HTTP, HTTPS, FTP, SNMP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP
		Deployment	System logs
	Protection	Protection	Reverse Polarity Protection
	Mounting	Flush-mounted	by 2 screws on the base of the module
	Connection terminal	Ethernet ports	2 x RJ45, 10/100Mbps adaptive
	Operating and display elements	Ports	Wiegand port, RS485 port
		Sensors Viewing Angle TIS Bus Upgrading	Infrared, Light, 116°(H) / 60°(V) TIS protocol messages and commands Over web
	Functions	HD picture reception Two-way audio communication Speaker Microphone Door entry	H.264, H.265, up to 1920x1080p resolution, SIP v1 (RFC2543), SIP v2 (RFC3261) Dual speakers, 8 / 2W -40dB Auto-night mode with LED illumination, Auto- white balance.
		RF card reader Compatibility	13.56MHz & 125kHz 3rd-Party-Video components.
	Weight	Without packaging	1.2 KG
	Dimensions	Length x Width x Height	130mm x 35mm x 280mm
	Housing	Materials	Fireproof ABS, Water-proof & Dust-proof IP65
		Casing color Base color IP rating	Gray White Black IP 20



Copyright © 2020 TIS, All Rights Reserved

TIS Logo is a Registered Trademark of Texas Intelligent System LLC in the United States of America. This company takes TIS Control Ltd. in other countries. All of the Specifications are subject to change without notice.

TEXAS INTELLIGENT SYSTEM LLC
SUITE# 610, 860 NORTH DOROTHY DR
RICHARDSON
TX 75081.USA

TIS CONTROL LIMITED
RM 1502-p9 Easey CommBldg
253-261 Hennessy Rd Wanchai
Hong Kong

TIS VIDEO DOOR PHONE


RF-enabled Intercom with Flush Buttons

Model: TIS-AP-CDM-18



PRODUCT SPECIFICATIONS

🌡️	Temperature Range	Operation	-20° ... 55°C
		Storage	-40° ... 70°C
💧	Air humidity	<85% non-condensing	



Copyright © 2020 TIS, All Rights Reserved
 TIS Logo is a Registered Trademark of Texas Intelligent System LLC in the United States of America. This company takes TIS Control Ltd. in other countries. All of the Specifications are subject to change without notice.

TEXAS INTELLIGENT SYSTEM LLC
 SUITE# 610, 860 NORTH DOROTHY DR
 RICHARDSON
 TX 75081.USA

TIS CONTROL LIMITED
 RM 1502-p9 Easey CommBldg
 253-261 Hennessy Rd Wanchai
 Hong Kong